

# TEST REPORT



**Add value.  
Inspire trust.**

## TÜV SÜD Industrie Service GmbH

Department of Chemical Analysis  
Ridlerstraße 65  
80339 Munich, Germany

Report No.: **23-C1545-1**  
Client: Curecrete Distribution, Inc.  
1203 W. Spring Creek Place  
Springville, Utha 84663  
USA  
Name of product: **Ashford Formula**  
Date of receipt: 2023/08/17  
Testing period: 2023/08/17 -2023/08/23  
Test Standards: TM 14 "Silicate-based chemical surface densifier"  
Issue 01/19  
Internal laboratory no.: 20230822333

Date: 2023-08-25

Our reference:  
IS-USL-MUC/HS  
test report 23-C1545-1.docx

### Results:


All tested requirements for the award of the TÜV SÜD mark "Low emissions, Pollutant tested and Production monitored" for the product group TM 14 " Silicate-based chemical surface densifier" edition 01-2019 were met.

This Document consists of  
2 pages.  
Page 1 of 2

Excerpts from this document  
may only be reproduced and  
used for advertising purposes  
with the express written  
approval of  
TÜV SÜD Industrie Service  
GmbH.

The test results refer  
exclusively to the units  
under test.

  
(Dipl.-Ing. Gabriele Glomsda)  
Head of Department

  
(Dipl.-Ing. (FH) Holger Struwe)  
Technical expert building products



**Headquarters: Munich**  
Trade Register Munich HRB 96 869  
VAT ID No. DE129484218  
Information pursuant to § 2 [1] DL-InfoV  
(Germany) at [tuvsud.com/imprint](http://tuvsud.com/imprint)

**Supervisory Board:**  
Reiner Block (Chairman)  
**Board of Management:**  
Ferdinand Neuwieser (CEO)  
Thomas Kainz  
Simon Kellerer

**TÜV SÜD Industrie Service GmbH**  
Abteilung Chemische Analytik  
Ridlerstrasse 65  
80339 Munich  
Germany

[tuvsud.com/de-is](http://tuvsud.com/de-is)  
Phone: +49 89 5190-4001





## 1 Sample Information

Sample name: **Ashford Formula**  
Date of production: 2023/08/07  
Place of production: 1203 Spring Creek Place, Springville, Utah 84663, USA  
Batch No.: AF0101080723  
Name of sampler: Sterling Carman (Curecrete)  
Place of sampling: Production tank (Curecrete)  
Type of sampling: 0,47 litre container  
Specification of sample: Silicate-based chemical surface densifier

## 2 Methods and measured values

### 2.1 Volatile organic compounds

Parameter	Testing method	Limit value <sup>1</sup> [mg/kg]	Measured value [mg/kg]
Total VOC	DIN EN ISO 17895:2005-06 (Headspace-GC-MS)	≤ 500	< 100

### 2.2 Semi-volatile organic compounds

Parameter	Testing method	Limit value <sup>1</sup> [mg/kg]	Measured value [mg/kg]
SVOC <sup>1</sup>	SAA-L-1516:2021-11 (Solvent extraction/GC-MS)	≤ 500	< 100

<sup>1</sup> SVOC: quantification of semi-volatile substances in the retention range C14 and C22

#### Notes:

Unless otherwise agreed, declared for the individual case, or normatively specified, PASS or FAIL verdicts are given based on the measured value without any considerations of measurement uncertainties (decision rule). Every test method has a measurement uncertainty which has been evaluated by the laboratory and is available on request. By taking measurement uncertainties into account, it might happen that measured values can neither be assessed as PASS nor as FAIL. Please inform us if you intend to use a different decision rule as part of your own conformity assessment. We are glad to provide you with the relevant information on the expanded measurement uncertainty.