

# CRETE STRIP™ FS

A FRESH START FOR CONCRETE SURFACES



## Product Description

**CreteStrip FS™** is a concentrated stripper formulated to give concrete floors a **fresh start** in preparation for densification or restoration. CreteStrip FS is designed for concrete and terrazzo floors, aiding in the quick and effective removal of acrylic floor coatings, acrylic curing compounds, waxes, carpet and tile mastic, paint, tire marks, and more!

### FEATURES

- Short dwell time:  
**Floor Finishes:** Effective within **5 minutes**  
**Guard Products:** Effective within **1 minute**
- Mild fragrance
- Low-foaming
- Low VOCs
- Cost effective
- Does not damage vinyl
- Does not contain ammonia
- Does not soften concrete



## Product Selection Guide

Substance for Removal	CreteStrip FS Fresh Start	CreteStrip Original
Acrylic Floor Coatings	Highly Effective	Effective
Carpet & Tile Mastic	Highly Effective	Effective
Construction Chalk	Highly Effective	Highly Effective
Oil & Grease Stains	Highly Effective	Highly Effective
Tire Marks	Highly Effective	Highly Effective
Waxes	Highly Effective	Highly Effective
Acrylic Curing Compounds	Effective	Effective
Paint	Moderately Effective	Moderately Effective
Spray Adhesive	Moderately Effective	Highly Effective
Tape Residue	Mildly Effective	Effective
Asphalt Residue	Ineffective	Moderately Effective
Permanent Marker Ink	Ineffective	Ineffective
Spray Paint	Ineffective	Moderately Effective



## Technical Info

<b>Form:</b>	Clear, yellow liquid
<b>Odor:</b>	Mild scent
<b>Flash point:</b>	220°F (104.4°C)
<b>Freezing:</b>	5°F (-15°C) If product freezes, agitate to re-emulsify. Can withstand 1 freeze-thaw cycle.
<b>pH:</b>	11.8 - 12.2 (Concentrate) 11.1 - 11.4 (Diluted for use)
<b>Packaging:</b>	1 gal (3.79 L) Jug 5 gal (18.9 L) Pail 55 gal (208.2 L) Drum
<b>Storage Life:</b>	2 years
<b>Dilution:</b>	CreteStrip FS : Water (1:20) <b>7 oz : 1 gal   55 mL : 1 L</b>
<b>Coverage:</b>	100 ft <sup>2</sup> /gal (6.7 m <sup>2</sup> /L)



## Application Instructions

**Area Preparation:** Sweep or dust mop the floor thoroughly. Place “Wet Floor” caution signs where necessary as the stripper solution becomes very slippery when in use.

**Application:** Dilute CreteStrip FS 1:20 with water. Apply the diluted stripper solution with a mop at a coverage rate of 100 ft<sup>2</sup>/gal (6.7 m<sup>2</sup>/L). The floor should be uniformly wet.

Allow the stripper solution to penetrate for 5-10 minutes to adequately soften any existing finishes or substances.

Apply additional stripper solution to areas that appear to be drying out. Do not allow stripper solution to dry on the floor surface. If

allowed to dry, it can attach to the floor and become difficult to remove.

Use a low-speed floor buffer (175 rpm) with a black stripping pad to thoroughly remove the old floor coating.

**Removal:** Pick up the soiled solution with a wet vacuum or auto scrubber. Flood-rinse the floor with clean water and remove with a wet vacuum or auto scrubber.

Feel the floor to check for any remaining residue. If residue is present, repeat **Step 8** to ensure complete removal.

Observe the floor for any remaining floor coatings and repeat **Steps 4-9** as necessary to fully remove.

Dispose of soiled solution in accordance with local/regional/national/international regulations.

Contact Curecrete for more information on supporting products:

- Ashford Formula™
- CreteClean Plus with Scar Guard™
- CreteClean Plus with Scar Guard - Single Dose™
- CreteFill Pro Series™ Joint Fillers and Repair Products
- CreteStrip™
- Diamonds & Dyes
- KickStart™
- RetroGuard™
- RetroPel™
- RetroPlate®
- SaltSlayer™
- SlurryDry™



## Warranty, Technical Assistance, & SDS

### WARRANTY

Manufacturer warrants this product to be free from defects. Where permitted by law, no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose. The purchaser shall be responsible to perform their own tests to determine the suitability of this product for their particular purpose. Liability shall be limited in all events to supplying sufficient product to re-treat the specific areas to which defective product has been applied. Acceptance and use of this product absolves supplier from any liability, from whatever source, including liability for incidental, consequential or resultant damages, whether due to breach of warranty, negligence or extended by representatives of CreteStrip FS, its distributors, applicators or dealers.

### TECHNICAL SERVICES & EMERGENCY CONTACT

Contact Curecrete at **(801) 489-5663** or toll free at **(800) 998-5664** or by email at [techsupport@curecrete.com](mailto:techsupport@curecrete.com).

**For emergency information, call (801) 629-0667.**

### SAFETY DATA SHEET (SDS)

For SDS information, please [click here](#) or scan the code provided.

