

# CRETE STRIP



## Product Description

**CreteStrip™** is a chemical agent specifically designed to remove residue and coatings from concrete and masonry surfaces in preparation for the application of the Ashford Formula™ or simply for aesthetics purposes.

### CreteStrip REMOVES:

- Acrylic Curing Compounds
- Old, Yellowed Acrylic Coatings
- Waxes, Paint, & Tire Marks
- Carpet and Tile Mastic
- Asphalt Residue
- Construction Chalk
- Tape Residue

### CreteStrip SUBSTANTIALLY LIGHTENS:

- Oil and Grease Stains
- Permanent Marker Ink



## Product Benefits

- ✓ Easy to Apply
- ✓ Works Fast. *Does its work in 30 minutes!*
- ✓ Requires little scrubbing. *Works chemically.*
- ✓ Low Price. *Less costly than many non-hazardous solutions.*



## Directions for Use

### SURFACE ANALYSIS

Often it is impossible to know the condition of the surface before an acrylic coating is removed. Treat a small test area to ensure that the results will be satisfactory. CreteStrip can be diluted with water (1:1 ratio), however, a sample test area should be performed to determine if a diluted formulation will effectively remove the material to be stripped. Applying product thinly, unevenly, or removing it too quickly may necessitate more than one application, increasing material and labor costs. It is highly recommended that the product be applied exactly as instructed to avoid unnecessary expenses.

**Note:** If you are preparing the floor for densification, be sure to test all areas of the concrete floor surface for water penetration. Any areas that will not readily accept water will require additional stripping until the floor is totally bare of any acrylic residue.



## Technical Info +

<b>Preparation</b>	CreteStrip must be mechanically blended before each use.
<b>Form</b>	Amber Liquid
<b>Weight</b>	10 lbs/gal (1.2 kg/L)
<b>Flash Point</b>	>123°F (50.6°C)
<b>pH</b>	6.59
<b>Packaging</b>	55 gallon (208 L) Drum 5 gallon (19 L) Pail 1 gallon (3.78 L) Container
<b>Coverage</b>	200 ft <sup>2</sup> /gal (5 m <sup>2</sup> /L)
<b>Storage Life</b>	One (1) year
<b>Thinners*</b>	Water (1:1 ratio)
<b>Applications</b>	Dependent upon type, condition, and millimeter thickness of material to be stripped.

\*CreteStrip can be diluted with water (1:1 ratio); a test sample should be done to determine if a diluted formulation will effectively remove the unwanted material.

### APPLICATION FOR GENERAL REMOVAL

**Area Preparation:** Sweep the area that is to be stripped.

**Application:** Apply CreteStrip onto the surface with a sprayer or mop at a rate of 200 ft<sup>2</sup>/gal (5m<sup>2</sup>/L). Use stiff-bristle brooms to work CreteStrip into the concrete surface and to distribute product evenly. Let product sit for a **full 30 minutes** before removing. Add CreteStrip as often as necessary to keep the surface wet for the entire 30 minutes. Exercise caution when using CreteStrip on areas adjacent to surfaces that could be damaged if exposed to it.

**Removal:** After 30 minutes, immediately remove all CreteStrip surface residue with an automatic scrubber or wet/dry vacuum, and a high-pH detergent, such as the recommended **CreteClean Plus with Scar Guard™**, to neutralize any areas treated with CreteStrip. Scrub all treated surfaces twice. On the third pass, use the vacuum or a squeegee to pick up any remaining detergent and water mixture until the floor is completely clean. Rinse all treated areas. Dispose contents in accordance with all local, state and federal regulations. Flush all scrubbing equipment thoroughly with fresh water.

**Warning:** Avoid excessive breathing of vapors or mist, especially in poorly ventilated areas. Avoid contact with eyes, skin or clothing. Wash thoroughly after handling.

## APPLICATION FOR OIL STAIN REMOVAL

**Product Preparation:** When using CreteStrip for oil stain removal, dilute CreteStrip with water at a ratio of 1:1.

**Application:** Spray or pour the diluted CreteStrip onto the surface. Use stiff-bristle push brooms to work the solution into the concrete surface. Let the solution dwell for at least 45 minutes.

**Removal:** Using a wet/dry vacuum or auto-scrubber, thoroughly remove all CreteStrip residue. Place a solution of detergent and water onto the surface, re-scrub the floor, then remove the soap solution with a wet/dry vacuum or an auto-scrubber. Do a final clean rinse with water.



## Warranty, Technical Assistance & SDS Info

### WARRANTY

Curecrete warrants this product to be free from defects. Where permitted by law, no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose. The purchaser shall be responsible to perform their own tests to determine the suitability of this product for their particular purpose. Liability shall be limited in all events to the supplying sufficient product to re-treat the specific areas to which defective product has been applied. Acceptance and use of this product absolves the manufacturer/supplier from any liability, from whatever source, including liability for incidental, consequential or resultant damages, whether due to breach of warranty, negligence or extended by representatives of Curecrete, its distributors, applicators or dealers.

### TECHNICAL SERVICES & EMERGENCY CONTACT

For Technical Assistance, contact Curecrete at **(801) 489-5663**, toll free at **(800) 998-5664** or by email at **techsupport@curecrete.com**.

**For emergency information, call (801) 629-0667.**

### Safety Data Sheet (SDS)

For SDS information, please [click here](#) or scan the code provided.

