

Safety Data Sheet acc. to OSHA HCS

Printing date 01/24/2022

Reviewed on 01/24/2022

1 Identification

- **Product identifier**
- **Trade name:** CreteStrip FSTM Fresh Start
- **Application of the substance / the mixture** Floor Stripper
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Curecrete Chemical Company
1203 Spring Creek Place
Springville, UT 84663
USA
techsupport@curecrete.com
(801) 489-5663
- **Information department:** Technical Services
- **Emergency telephone number:**
(800) 633-8253 (United States/Canada)
+1 (801) 629-0667 International Emergency Number

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.
Acute Tox. 4 H312 Harmful in contact with skin.
Acute Tox. 4 H332 Harmful if inhaled.
Flam. Liq. 4 H227 Combustible liquid.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05 GHS07

- **Signal word** Danger

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/24/2022

Reviewed on 01/24/2022

Trade name: CreteStrip FS

(Contd. of page 1)

- **Hazard-determining components of labeling:**

2-aminoethanol
Benzyl alcohol
2-butoxyethanol

- **Hazard statements**

Combustible liquid.
Harmful if swallowed, in contact with skin or if inhaled.
Causes severe skin burns and eye damage.

- **Precautionary statements**

Keep away from flames and hot surfaces. – No smoking.
Do not breathe dusts or mists.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Call a poison center/doctor if you feel unwell.
If swallowed: Rinse mouth. Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Immediately call a poison center/doctor.
Specific treatment (see on this label).
Take off contaminated clothing and wash it before reuse.
Wash contaminated clothing before reuse.
In case of fire: Use CO₂, powder or water spray to extinguish.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**

Health = 3
Fire = 1
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**

Health = 3
Fire = 1
Reactivity = 0

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

100-51-6 Benzyl alcohol	30-60%
141-43-5 2-aminoethanol	30-60%
111-76-2 2-butoxyethanol	7-13%

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/24/2022

Reviewed on 01/24/2022

Trade name: CreteStrip FS

(Contd. of page 2)

· Non-hazardous ingredients

1300-72-7 sodium xylenesulphonate	1-5%
68131-39-5 Alcohols, C12-15, ethoxylated	1-5%

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Immediately call a doctor.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

· Information for doctor:

· Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture No further relevant information available.

· Advice for firefighters

· Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:

100-51-6 Benzyl alcohol: 30 ppm

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/24/2022

Reviewed on 01/24/2022

Trade name: CreteStrip FS

(Contd. of page 3)

141-43-5 2-aminoethanol: 6 ppm

111-76-2 2-butoxyethanol: 60 ppm

· **PAC-2:**

100-51-6 Benzyl alcohol: 52 ppm

141-43-5 2-aminoethanol: 170 ppm

111-76-2 2-butoxyethanol: 120 ppm

· **PAC-3:**

100-51-6 Benzyl alcohol: 740 ppm

141-43-5 2-aminoethanol: 1,000 ppm

111-76-2 2-butoxyethanol: 700 ppm

7 Handling and storage

· **Handling:**· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:** No special measures required.· **Conditions for safe storage, including any incompatibilities**· **Storage:**· **Requirements to be met by storerooms and receptacles:** No special requirements.· **Information about storage in one common storage facility:** Not required.· **Further information about storage conditions:** Keep receptacle tightly sealed.· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.· **Control parameters**· **Components with limit values that require monitoring at the workplace:****100-51-6 Benzyl alcohol**

WEEL Long-term value: 10 ppm

141-43-5 2-aminoethanolPEL Long-term value: 6 mg/m³, 3 ppmREL Short-term value: 15 mg/m³, 6 ppmLong-term value: 8 mg/m³, 3 ppmTLV Short-term value: 15 mg/m³, 6 ppmLong-term value: 7.5 mg/m³, 3 ppm**111-76-2 2-butoxyethanol**PEL Long-term value: 240 mg/m³, 50 ppm

Skin

REL Long-term value: 24 mg/m³, 5 ppm

Skin

TLV Long-term value: 97 mg/m³, 20 ppm

BEI

(Contd. on page 5)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/24/2022

Reviewed on 01/24/2022

Trade name: CreteStrip FS

(Contd. of page 4)

- **Ingredients with biological limit values:**

- **111-76-2 2-butoxyethanol**

- BEI 200 mg/g creatinine

- Medium: urine

- Time: end of shift

- Parameter: Butoxyacetic acid with hydrolysis

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.

- Immediately remove all soiled and contaminated clothing.

- Wash hands before breaks and at the end of work.

- Avoid contact with the eyes and skin.

- **Breathing equipment:**

- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

- **Form:** Liquid

- **Color:** Green

- **Odor:** Fruit-like

- **Odor threshold:** Not determined.

- **pH-value at 20 °C (68 °F):** 12-13

- **Change in condition**

- **Melting point/Melting range:** Undetermined.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/24/2022

Reviewed on 01/24/2022

Trade name: CreteStrip FS

(Contd. of page 5)

Boiling point/Boiling range:	170 °C (338 °F)
· Flash point:	65 °C (149 °F)
· Flammability (solid, gaseous):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Not determined.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	13 Vol %
· Vapor pressure at 20 °C (68 °F):	1.2 hPa (0.9 mm Hg)
· Density at 20 °C (68 °F):	1.02 g/cm ³ (8.5119 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	67-133 %
VOC content:	67-100 %
	1,356.6 g/l / 11.32 lb/gal
Solids content:	0.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**
- 100-51-6 Benzyl alcohol**
- Oral LD50 1,230 mg/kg (rat)
- Dermal LD50 2,000 mg/kg (rabbit)

(Contd. on page 7)

— US —

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/24/2022

Reviewed on 01/24/2022

Trade name: CreteStrip FS

(Contd. of page 6)

141-43-5 2-aminoethanol

Oral LD50 2,050 mg/kg (rat)

Dermal LD50 1,000 mg/kg (rabbit)

111-76-2 2-butoxyethanol

Oral LD50 1,480 mg/kg (rat)

Dermal LD50 400 mg/kg (rab)

· **Primary irritant effect:**· **on the skin:** Caustic effect on skin and mucous membranes.· **on the eye:** Strong caustic effect.· **Sensitization:** No sensitizing effects known.· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· **Carcinogenic categories**· **IARC (International Agency for Research on Cancer)**

111-76-2 2-butoxyethanol: 3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**· **Aquatic toxicity:** No further relevant information available.· **Persistence and degradability** No further relevant information available.· **Behavior in environmental systems:**· **Bioaccumulative potential** No further relevant information available.· **Mobility in soil** No further relevant information available.· **Additional ecological information:**· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.· **Other adverse effects** No further relevant information available.

— US —

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/24/2022

Reviewed on 01/24/2022

Trade name: CreteStrip FS

(Contd. of page 7)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- **UN-Number**
- **DOT, IMDG, IATA** UN3267
- **UN proper shipping name**
- **DOT** Corrosive liquid, basic, organic, n.o.s.
- **IMDG, IATA** CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.
- **Transport hazard class(es)**

· **DOT**

- **Class** 8 Corrosive substances
- **Label** 8

· **IMDG, IATA**

- **Class** 8 Corrosive substances
- **Label** 8
- **Packing group**
- **DOT, IMDG, IATA** III
- **Environmental hazards:** Not applicable.
- **Special precautions for user** Warning: Corrosive substances
- **Hazard identification number (Kemler code):** 80
- **EMS Number:** F-A,S-B
- **Segregation groups** Alkalis
- **Stowage Category** A
- **Stowage Code** SW2 Clear of living quarters.
- **Segregation Code** SG35 Stow "separated from" SGG1-acids
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.
- **Transport/Additional information:**
- **DOT**
- **Quantity limitations** On passenger aircraft/rail: 5 L
On cargo aircraft only: 60 L

(Contd. on page 9)

— US —

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/24/2022



Reviewed on 01/24/2022

Trade name: CreteStrip FS

(Contd. of page 8)

- **IMDG**
- **Limited quantities (LQ)** 5L
- **Excepted quantities (EQ)** Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
- **UN "Model Regulation":** UN 3267 CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S., 8, III

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.
- **Sara**
- **Section 355 (extremely hazardous substances):**
None of the ingredients is listed.
- **Section 313 (Specific toxic chemical listings):**
111-76-2 2-butoxyethanol
- **TSCA (Toxic Substances Control Act):**
All components have the value ACTIVE.
- **Hazardous Air Pollutants**
None of the ingredients is listed.
- **Proposition 65**
- **Chemicals known to cause cancer:**
None of the ingredients is listed.
- **Chemicals known to cause reproductive toxicity for females:**
None of the ingredients is listed.
- **Chemicals known to cause reproductive toxicity for males:**
None of the ingredients is listed.
- **Chemicals known to cause developmental toxicity:**
None of the ingredients is listed.
- **Carcinogenic categories**
- **EPA (Environmental Protection Agency)**
111-76-2 2-butoxyethanol: NL
- **TLV (Threshold Limit Value)**
111-76-2 2-butoxyethanol: A3
- **NIOSH-Ca (National Institute for Occupational Safety and Health)**
None of the ingredients is listed.
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**


 GHS05 GHS07
- **Signal word** Danger
- **Hazard-determining components of labeling:**
2-aminoethanol
Benzyl alcohol
2-butoxyethanol

(Contd. on page 10)

— US —

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/24/2022

Reviewed on 01/24/2022

Trade name: CreteStrip FS

(Contd. of page 9)

- **Hazard statements**

Combustible liquid.
Harmful if swallowed, in contact with skin or if inhaled.
Causes severe skin burns and eye damage.

- **Precautionary statements**

Keep away from flames and hot surfaces. – No smoking.
Do not breathe dusts or mists.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Call a poison center/doctor if you feel unwell.
If swallowed: Rinse mouth. Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Immediately call a poison center/doctor.
Specific treatment (see on this label).
Take off contaminated clothing and wash it before reuse.
Wash contaminated clothing before reuse.
In case of fire: Use CO₂, powder or water spray to extinguish.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Technical Services

- **Contact:** Dave Hoyt

- **Date of preparation / last revision** 01/24/2022 / -

- **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flam. Liq. 4: Flammable liquids – Category 4
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Eye Dam. 1: Serious eye damage/eye irritation – Category 1