



Product Description

RF™ **Strip & Prepare** is a concentrated stripper formulated to give concrete floors a **fresh start** in preparation for densification or restoration. RF Strip & Prepare is designed for concrete and terrazzo floors, aiding in the quick and effective removal of acrylic floor coatings, acrylic curing compounds, waxes, carpet and tile mastic, paint, tire marks, and more!

FEATURES

- Short dwell time:
Floor Finishes: Effective within **5 minutes**
Guard Products: Effective within **1 minute**
- Mild fragrance
- Low-foaming
- Low VOCs
- Cost effective
- Does not damage vinyl
- Does not contain ammonia
- Does not soften concrete



Product Selection Guide

Substance for Removal	RF Strip & Prepare	CreteStrip Original
Acrylic Floor Coatings	Highly Effective	Effective
Carpet & Tile Mastic	Highly Effective	Effective
Construction Chalk	Highly Effective	Highly Effective
Oil & Grease Stains	Highly Effective	Highly Effective
Tire Marks	Highly Effective	Highly Effective
Waxes	Highly Effective	Highly Effective
Acrylic Curing Compounds	Effective	Effective
Paint	Moderately Effective	Moderately Effective
Spray Adhesive	Moderately Effective	Highly Effective
Tape Residue	Mildly Effective	Effective
Asphalt Residue	Ineffective	Moderately Effective
Permanent Marker Ink	Ineffective	Ineffective



Technical Info

Form:	Clear, yellow liquid
Odor:	Mild scent
Flash point:	220°F (104.4°C)
Freezing:	5°F (-15°C) If product freezes, agitate to re-emulsify. Can withstand 1 freeze-thaw cycle.
pH:	11.8 - 12.2 (Concentrate) 11.1 - 11.4 (Diluted for use)
Packaging:	1 gal (3.79 L) Jug 5 gal (18.9 L) Pail 55 gal (208.2 L) Drum
Storage Life:	2 years
Dilution:	RF Strip & Prepare : Water (1:20) 7 oz : 1 gal 55 mL : 1 L
Coverage:	100 ft ² /gal (2.45 m ² /L)



Application Instructions

PREPARATION

Sweep or dust mop the floor thoroughly. Place "Wet Floor" caution signs where necessary as the stripper solution becomes very slippery when in use.

STANDARD APPLICATION PROCEDURE

Dilute RF Strip & Prepare 1:20 with water (7 oz:1 gal | 55 mL:1 L).

Pour the diluted stripper solution onto the floor at a coverage rate of 100 ft²/gal (2.45 m²/L). Spread and agitate the solution with a mop or push broom. The floor should be uniformly wet.

Allow the stripper solution to penetrate for 5-10 minutes to adequately soften any existing finishes or substances.

Apply additional stripper solution to areas that appear to be drying out. Do not allow stripper solution to dry on the floor surface. If allowed to dry, it can attach to the floor and become difficult to remove.

Use a low-speed floor buffer (175 rpm) or an auto scrubber with a black stripping pad to thoroughly remove the old floor coating.

REMOVAL

Pick up the soiled solution with a wet vacuum or auto scrubber.

Flood-rinse the floor with clean water and remove with a wet vacuum or auto scrubber.

Feel the floor to check for any remaining residue. If residue is present, repeat flood-rinse step.

Observe the floor for any remaining floor coatings and repeat steps as necessary to fully remove.

Dispose of soiled solution in accordance with local/regional/national/international regulations.



**Warranty, Technical Assistance,
& Safety Data Sheet (SDS)**

WARRANTY

Manufacturer warrants this product to be free from defects. Where permitted by law, no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose. The purchaser shall be responsible to perform their own tests to determine the suitability of this product for their particular purpose. Liability shall be limited in all events to supplying sufficient product to re-treat the specific areas to which defective product has been applied. Acceptance and use of this product absolves supplier from any liability, from whatever source, including liability for incidental, consequential or resultant damages, whether due to breach of warranty, negligence or extended by representatives of RF Strip & Prepare, its distributors, applicators or dealers.

TECHNICAL SERVICES & EMERGENCY CONTACT

Contact Curecrete at (801) 489-5663 or toll free at (800) 998-5664, or by email at techsupport@curecrete.com.

For emergency information, call (801) 629-0667.

SAFETY DATA SHEET (SDS)

For SDS information, scan the code provided.



SUPPORTING PRODUCTS

Contact Curecrete for more information on these supporting products:

- RF Acid & Stain Defender
- RF Densify & Harden
- RF Grind & Enhance
- RF Hard Surface Cleaner
- RF Hard Surface Cleaner - Single Dose
- RF Water & Oil Defender